









Immune to LIGHTNING DAMAGE.



WATER and HEAVY WASHDOWN reliability.



TRANSIENT VOLTAGE and R.F.I. resistant.



Protected against RODENT DAMAGE.




Your <u>lowest possible</u> MAINTENANCE COST.



Retrofit Kit Includes:





- Copper Tubing

 (to place totalizer up to
 20 ft. from edge of deck)
- Base Plates
- Leveling Bolts
- Anchor Bolts
- Load Buttons
- Load Plates
- Accessory Kit









| MODE | TONS CAPACITY | NO. OF MODULES | NO. OF LOAD CELLS | CELL CAPACITY | SHIPPING WEIGHT |
|--------|---------------|----------------|-------------------|---------------|-----------------|
| GTSC- | 4 60 | 1 | 4 | 50,000 lb | 520 lb |
| GTSC- | 6 80 | 2 | 6 | 50,000 lb | 725 lb |
| GTSC- | 3 100 | 3 | 8 | 50,000 lb | 1,050 lb |
| GTSC-1 | 0 100 | 4 | 10 | 50,000 lb | 1,175 lb |
| GTSC-1 | 2 120 | 5 | 12 | 50,000 lb | 1,350 lb |

| MODEL | DESCRIPTION | SHIPPING WEIGHT |
|--------|---|-----------------|
| GRSKIT | Optional Guardian® restraint system kit, including: 2 lateral stabilizer rod assemblies and mounting brackets, plus 2 longitudinal stabilizer rod assemblies and anchor plates. | 265 lb |



Cardinal's model SST Hydraulic Load Cell meets or exceeds. Class IIIL, 10 000 division accuracy requirements in accordance with the NIST Handbook 44. A Certificate of Conformance Number **05-076**, was issued under the National Type Evaluation Program (NTEP) of the National Conference on Weights and Measures. The CC specifies the maximum number of scale divisions (n-max), load cell verification interval (v-min), and capacities for the Model SST load cell family.





Cardinal Scale reserves the right to improve, enhance, or modify features and specifications without prior notice.

Sold By:

Cardinal Scale Manufacturing Co.
203 E. Daugherty, Webb City, MO 64870 USA
Ph: 417-673-4631 or 800-441-4237 • Fax: 417-673-5001

www.CardinalScale.com